

Product: Hydrogen Page :1/4

MSDS Nr : 067A AL Version : 1.01 Date : 31/07/2002

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MSDS Nr 067A_AL

Product name Hydrogen

Chemical formula H2

Company identification see heading and/or footer

see paragraph 16 "OTHER INFORMATION"

Emergency phone numbers see heading and/or footer

see paragraph 16 "OTHER INFORMATION"

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation Substance.

Components/Impurities Contains no other components or impurities which will influence the classification of the

product.

CAS Nr 01333-74-0 EEC Nr (from EINECS) 215-605-7

3 HAZARDS IDENTIFICATION

Hazards identification Compressed gas

Extremely flammable

4 FIRST AID MEASURES

Inhalation In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Ingestion Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products None

Suitable extinguishing media All known extinguishants can be used. Specific methods If possible, stop flow of product.

Move away from the container and cool with water from a protected position.

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive

re-ignition may occur. Extinguish any other fire.

Product : Hydrogen Page :2/4

Special protective equipment for fire fighters

In confined space use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be

safe.

Evacuate area.

Ensure adequate air ventilation.
Eliminate ignition sources.
Try to stop release.

Environmental precautions Try to stop rele Clean up methods Ventilate area.

7 HANDLING AND STORAGE

Handling and storage Ensure equipment is adequately earthed.

Suck back of water into the container must be prevented.

Purge air from system before introducing gas.

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt. Keep away from ignition sources (including static discharges). Segregate from oxidant gases and other oxidants in store. Refer to supplier's container handling instructions. Keep container below 50° C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection Ensure adequate ventilation.

Do not smoke while handling product.

9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight 2

Melting point -259 °C

Boiling point -253 °C

Critical temperature -240 °C

Relative density, gas 0.07 (air=1)

Relative density, liquid 0.07 (water=1)

Vapour Pressure 20°C Not applicable.

Solubility mg/l water 1.6 mg/l

Product: Hydrogen Page :3/4

Appearance/Colour Colourless gas

Odour None

Autoignition temperature 560 °C

Flammability range 4-75 vol% in air.

Other data Burns with a colourless invisible flame.

10 STABILITY AND REACTIVITY

Stability and reactivity Can form explosive mixture with air.

May react violently with oxidants.

11 TOXICOLOGICAL INFORMATION

General No toxicological effects from this product.

12 ECOLOGICAL INFORMATION

General No known ecological damage caused by this product.

13 DISPOSAL CONSIDERATIONS

General Do not discharge into areas where there is a risk of forming an explosive mixture with air.

Waste gas should be flared through a suitable burner with flash back arrestor.

Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

14 TRANSPORT INFORMATION

Proper shipping name Hydrogen, compressed

UN Nr 1049
Class/Div 2.1
ADR/RID Classification code 2, 1°F
ADR/RID Hazard Nr 23

Labelling ADR Label 3: flammable gas

Other transport information Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the

event of an accident or an emergency.

Before transporting product containers ensure that they are firmly secured and:

- cylinder valve is closed and not leaking

- valve outlet cap nut or plug (where provided) is correctly fitted

Product: Hydrogen Page :4/4

- valve protection device (where provided) is correctly fitted

- there is adequate ventilation.

- compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548 001-001-00-9.

EC Classification F+;R12

-Symbols F+: Extremely flammable
-Risk phrases R12 Extremely flammable.

-Safety phrases S9 Keep container in well ventilated place.

S16 Keep away from ignition sources - No smoking.

 $S33\ Take\ precautionary\ measures\ against\ static\ discharges.$

16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their

This MSDS is for information purposes only and is subject to change without notice. [Prior to purchase of products, please contact your local Air Liquide office for a complete MSDS (with Manufacturer's name and emergency phone number).]

End of document. Number of pages :4